

Working light LED 5000



The **working light LED 5000** is designed for wide area illumination. The swiveling tripod connector enables the lamp to be mounted on any standard tripod (also available for the standard german fire brigade tripod). It impresses with a light capacity of 5.000 lm and can be run with an operating voltage of 12V or 24V DC as it is used in typical vehicles. The current consumption is just 3A operated with 12V and 1,5A with 24V. The complete lamp weighs just 1,3 kg, measures 150mm length and a diameter of 109mm. It is available in different shapes. The coiled cord can be pulled up to 4m.

SPECIFICATIONS

Light output	: 5.000 lm
Operating voltage	: 12 or 24V DC
Current consumption	: 3,5 A (12V) / 1,75 A (24V)
Technique	: 4 circles of light 3 LEDs - Total 12 LEDs
Color temperature	: 6500 K
Housing	: aluminum
Front glass	: polycarbonate shock-insensitive
Resistance	: IP65
Dimensions	: Ø 109 mm x 150 mm
Weight lamp	: 1.300 g
Reflectors	: Spot Optic (ca. 9 °) Flood optics M (ca. 23 °) Flood optics L (ca. 40 °) Flood optics XL (ca. 120 °) (individually combined)
Cable weight	: 350 g
Cable length	: 4 m (extended)
Basic variant 12-24V	: Standard tripod shooting car plug

Optional accessories:

Vehicle recording
Magnetic 3-point with standard spigot
C16 plug 12/24V vehicle plug